

Ikke 30v



Oil Pattern Distance Forward Oil Total Tank Configuration 39 14.16 mL N/A Reverse Brush Drop Reverse Oil Total Tank A Conditioner

5.96 mL TERRAIN

39

Oil Per Board Volume Oil Total Tank B Conditioner 40 ul 20.12 mL ICE

START STOP LOADS SPEED BUFFER TANK CROSSED START END FEET T.OIL 1 3L 3R 4 14 3 A 140 0.0 5.9 5.9 5600 2 6L 6R 1 14 3 A 29 5.9 7.8 1.9 1160 3 7L 7R 1 14 3 A 27 7.8 9.7 1.9 1080 4 8L 8R 1 18 3 A 25 9.7 12.2 2.5 1000 5 10L 10R 3 18 3 A 63 12.2 19.8 7.6 2520 6 11L 11R 2 18 3 A 38 19.8 24.9 5.1 1520 7 12L 12R 1 22 3 A 17 24.9 28.		CTART	STOR	LOADS	CDEED	DITECED	TANK	CROSSED	CTART	ENID	FEET	T.OIL
2 6L 6R 1 14 3 A 29 5.9 7.8 1.9 1160 3 7L 7R 1 14 3 A 27 7.8 9.7 1.9 1080 4 8L 8R 1 18 3 A 25 9.7 12.2 2.5 1000 5 10L 10R 3 18 3 A 63 12.2 19.8 7.6 2520 6 11L 11R 2 18 3 A 38 19.8 24.9 5.1 1520 7 12L 12R 1 22 3 A 15 28.0 31.1 3.1 600		START		LUADS		BUFFER	IANK	CROSSED	START	END	FEET	
3 7L 7R 1 14 3 A 27 7.8 9.7 1.9 1080 4 8L 8R 1 18 3 A 25 9.7 12.2 2.5 1000 5 10L 10R 3 18 3 A 63 12.2 19.8 7.6 2520 6 11L 11R 2 18 3 A 38 19.8 24.9 5.1 1520 7 12L 12R 1 22 3 A 15 28.0 31.1 3.1 600	1	3L	3R	4	14	3	Α	140	0.0	5.9	5.9	5600
4 8L 8R 1 18 3 A 25 9.7 12.2 2.5 1000 5 10L 10R 3 18 3 A 63 12.2 19.8 7.6 2520 6 11L 11R 2 18 3 A 38 19.8 24.9 5.1 1520 7 12L 12R 1 22 3 A 17 24.9 28.0 3.1 680 8 13L 13R 1 22 3 A 15 28.0 31.1 3.1 600	2	6L	6R	1	14	3	Α	29	5.9	7.8	1.9	1160
5 10L 10R 3 18 3 A 63 12.2 19.8 7.6 2520 6 11L 11R 2 18 3 A 38 19.8 24.9 5.1 1520 7 12L 12R 1 22 3 A 17 24.9 28.0 3.1 680 8 13L 13R 1 22 3 A 15 28.0 31.1 3.1 600	3	7L	7R	1	14	3	Α	27	7.8	9.7	1.9	1080
6 11L 11R 2 18 3 A 38 19.8 24.9 5.1 1520 7 12L 12R 1 22 3 A 17 24.9 28.0 3.1 680 8 13L 13R 1 22 3 A 15 28.0 31.1 3.1 600	4	8L	8R	1	18	3	Α	25	9.7	12.2	2.5	1000
7 12L 12R 1 22 3 A 17 24.9 28.0 3.1 680 8 13L 13R 1 22 3 A 15 28.0 31.1 3.1 600	5	10L	10R	3	18	3	Α	63	12.2	19.8	7.6	2520
8 13L 13R 1 22 3 A 15 28.0 31.1 3.1 600	6	11L	11R	2	18	3	Α	38	19.8	24.9	5.1	1520
	7	12L	12R	1	22	3	Α	17	24.9	28.0	3.1	680
9 2L 2R 0 22 3 A 0 31.1 39.0 7.9 0	8	13L	13R	1	22	3	Α	15	28.0	31.1	3.1	600
	9	2L	2R	0	22	3	Α	0	31.1	39.0	7.9	0

	START	STOP	LOADS	SPEED	BUFFER	TANK	CROSSED	START	END	FEET	T.OIL
1	2L	2R	0	26	3	Α	0	39.0	22.0	-17.0	0
2	13L	13R	1	18	3	Α	15	22.0	19.5	-2.5	600
3	11L	11R	1	14	3	Α	19	19.5	17.6	-1.9	760
4	10L	10R	2	14	3	Α	42	17.6	13.7	-3.9	1680
5	9L	9R	2	14	3	Α	46	13.7	9.8	-3.9	1840
6	7L	7R	1	14	3	Α	27	9.8	7.9	-1.9	1080
7	2L	2R	0	14	3	Α	0	7.9	0.0	-7.9	0

Cleaner Ratio Main Mix 19:1 Forward
Cleaner Ratio Back End Mix 19:1 Reverse
Cleaner Ratio Back End Distance 59 Combined

Buffer RPM: 4 = 700 | 3 = 500 | 2 = 200 | 1 = 100

Kegel Kode: 4239 | Pattern designed for use in Kegel TRANSFER ROLLER/WIPER BAR machines. | This 39 foot pattern is moderately challenging: it's not too easy nor is it not too tough. This pattern should play somewhere between the extrame inside line and extreme outside line depending on specific lane surface characteristics.

Item	3L-7L:18L-18R	8L-12L:18L-18R	13L-17L:18L-18R	18L-18R:17R-13R	18L-18R:12R-8R	18L-18R:7R-3R
Description	Outside:Middle	Middle:Middle	Inside:Middle	Mlddle: Inside	Middle:Middle	Middle:Outside
Track Zone Ratio	4.38	1.5	1	1	1.5	4.38



