

Panttarit v3



Oil Pattern Distance Forward Oil Total Tank Configuration 43 13.32 mL N/A Reverse Brush Drop Reverse Oil Total Tank A Conditioner 38 10.48 mL TERRAIN Oil Per Board Volume Oil Total Tank B Conditioner 40 ul 23.8 mL CURVE

START STOP LOADS SPEED BUFFER TANK CROSSED START END FEET T.OIL 1 3L 3R 3 10 4 A 105 0.0 2.8 2.8 4200 2 4L 4R 2 14 3 A 66 2.8 6.7 3.9 2640 3 7L 7R 2 18 3 A 54 6.7 11.8 5.1 2160 4 10L 10R 1 18 3 A 21 11.8 14.3 2.5 840 5 11L 11R 2 18 3 A 38 14.3 19.4 5.1 1520 6 12L 12R 2 18 3 A 34 19.4 24.5 5.1 1360 7 13L 13R 1 18 3 A 15 24.5												
2 4L 4R 2 14 3 A 66 2.8 6.7 3.9 2640 3 7L 7R 2 18 3 A 54 6.7 11.8 5.1 2160 4 10L 10R 1 18 3 A 21 11.8 14.3 2.5 840 5 11L 11R 2 18 3 A 38 14.3 19.4 5.1 1520 6 12L 12R 2 18 3 A 34 19.4 24.5 5.1 1360 7 13L 13R 1 18 3 A 15 24.5 27.0 2.5 600		START	STOP	LOADS	SPEED	BUFFER	TANK	CROSSED	START	END	FEET	T.OIL
3 7L 7R 2 18 3 A 54 6.7 11.8 5.1 2160 4 10L 10R 1 18 3 A 21 11.8 14.3 2.5 840 5 11L 11R 2 18 3 A 38 14.3 19.4 5.1 1520 6 12L 12R 2 18 3 A 34 19.4 24.5 5.1 1360 7 13L 13R 1 18 3 A 15 24.5 27.0 2.5 600	1	3L	3R	3	10	4	Α	105	0.0	2.8	2.8	4200
4 10L 10R 1 18 3 A 21 11.8 14.3 2.5 840 5 11L 11R 2 18 3 A 38 14.3 19.4 5.1 1520 6 12L 12R 2 18 3 A 34 19.4 24.5 5.1 1360 7 13L 13R 1 18 3 A 15 24.5 27.0 2.5 600	2	4L	4R	2	14	3	Α	66	2.8	6.7	3.9	2640
5 11L 11R 2 18 3 A 38 14.3 19.4 5.1 1520 6 12L 12R 2 18 3 A 34 19.4 24.5 5.1 1360 7 13L 13R 1 18 3 A 15 24.5 27.0 2.5 600	3	7L	7R	2	18	3	Α	54	6.7	11.8	5.1	2160
6 12L 12R 2 18 3 A 34 19.4 24.5 5.1 1360 7 13L 13R 1 18 3 A 15 24.5 27.0 2.5 600	4	10L	10R	1	18	3	Α	21	11.8	14.3	2.5	840
7 13L 13R 1 18 3 A 15 24.5 27.0 2.5 600	5	11L	11R	2	18	3	Α	38	14.3	19.4	5.1	1520
	6	12L	12R	2	18	3	Α	34	19.4	24.5	5.1	1360
8 2L 2R 0 26 3 A 0 27.0 43.0 16.0 0	7	13L	13R	1	18	3	Α	15	24.5	27.0	2.5	600
	8	2L	2R	0	26	3	Α	0	27.0	43.0	16.0	0

2 15L 15R 2 22 3 A 22 34.0 27.8 -6.2 880 3 14L 14R 2 18 3 A 26 27.8 22.7 -5.1 1040 4 13L 13R 3 18 3 A 45 22.7 15.1 -7.6 1800 5 11L 11R 3 14 3 A 57 15.1 9.2 -5.9 2280 6 10L 10R 2 14 3 A 42 9.2 5.3 -3.9 1680 7 3L 3R 2 10 3 A 70 5.3 2.5 -2.8 2800		START	STOP	LOADS	SPEED	BUFFER	TANK	CROSSED	START	END	FEET	T.OIL
3 14L 14R 2 18 3 A 26 27.8 22.7 -5.1 1040 4 13L 13R 3 18 3 A 45 22.7 15.1 -7.6 1800 5 11L 11R 3 14 3 A 57 15.1 9.2 -5.9 2280 6 10L 10R 2 14 3 A 42 9.2 5.3 -3.9 1680 7 3L 3R 2 10 3 A 70 5.3 2.5 -2.8 2800	1	2L	2R	0	26	3	Α	0	43.0	34.0	-9.0	0
4 13L 13R 3 18 3 A 45 22.7 15.1 -7.6 1800 5 11L 11R 3 14 3 A 57 15.1 9.2 -5.9 2280 6 10L 10R 2 14 3 A 42 9.2 5.3 -3.9 1680 7 3L 3R 2 10 3 A 70 5.3 2.5 -2.8 2800	2	15L	15R	2	22	3	Α	22	34.0	27.8	-6.2	880
5 11L 11R 3 14 3 A 57 15.1 9.2 -5.9 2280 6 10L 10R 2 14 3 A 42 9.2 5.3 -3.9 1680 7 3L 3R 2 10 3 A 70 5.3 2.5 -2.8 2800	3	14L	14R	2	18	3	Α	26	27.8	22.7	-5.1	1040
6 10L 10R 2 14 3 A 42 9.2 5.3 -3.9 1680 7 3L 3R 2 10 3 A 70 5.3 2.5 -2.8 2800	4	13L	13R	3	18	3	Α	45	22.7	15.1	-7.6	1800
7 3L 3R 2 10 3 A 70 5.3 2.5 -2.8 2800	5	11L	11R	3	14	3	Α	57	15.1	9.2	-5.9	2280
	6	10L	10R	2	14	3	Α	42	9.2	5.3	-3.9	1680
8 2L 2R 0 10 3 A 0 2.5 0.0 -2.5 0	7	3L	3R	2	10	3	Α	70	5.3	2.5	-2.8	2800
	8	2L	2R	0	10	3	Α	0	2.5	0.0	-2.5	0

Cleaner Ratio Main Mix 19:1 Forward
Cleaner Ratio Back End Mix 19:1 Reverse
Cleaner Ratio Back End Distance 59 Combined
Buffer RPM: 4 = 700 | 3 = 500 | 2 = 200 | 1 = 100

Item	3L-7L:18L-18R	8L-12L:18L-18R	13L-17L:18L-18R	18L-18R:17R-13R	18L-18R:12R-8R	18L-18R:7R-3R
Description	Outside:Middle	Middle:Middle	Inside:Middle	MIddle: Inside	Middle:Middle	Middle:Outside
Track Zone Ratio	3.86	2.05	1.05	1.05	2.05	3.86



